

## POLYSEAMSEAL® All-Purpose Adhesive Caulk

### DESCRIPTION

LOCTITE® POLYSEAMSEAL® All-Purpose Adhesive Caulk is a premium grade water-based caulk designed to have the strength of an adhesive and the sealing characteristics of a caulk. POLYSEAMSEAL All-Purpose bonds to most indoor surfaces including wood, concrete, metal, ceramic, drywall, plaster, and some plastics. Easy to apply and tool. Environmentally safe, soap and water clean-up. Contains no silicone. Cured product is water-resistant, mold and mildew resistant and paintable

#### Available as:

Item #	Package	Size	Color
2139006	Squeeze Tube	5.5 oz	White
2154751	Plastic Cartridge	10 oz	White
2139007	Squeeze Tube	5.5 oz	Clear
2154740	Plastic Cartridge	10 oz	Clear
2137996	Plastic Cartridge	10 oz	Almond



### FEATURES & BENEFITS

- 2-in-1 product possesses both bonding and sealing capabilities
- Sealant is mold and mildew resistant
- Sealant is paintable with a latex paint
- Water resistant sealant works in high humidity environments once cured
- Low VOC content
- Easy clean up with soap and water
- Sealant remains flexible for a durable professional finish

### RECOMMENDED FOR

POLYSEAMSEAL® All-Purpose was designed to be a multiple use adhesive and caulk. Can be used for almost any household or remodeling project. Use for repairing or fixing loose moldings or tiles, securing backsplashes, setting sinks\*, repairing or concealing small cracks in plaster, drywall or around moldings and baseboards. POLYSEAMSEAL® All-Purpose can even help to lower energy costs by sealing air leaks around windows and door sand other utility and plumbing penetrations.

### LIMITATIONS

- Do not apply outdoors when rain or freezing temperatures are expected within 24 hours
- Do not use for architectural joints, horizontal joints subject to heavy abrasion or wear, expansion joints, or for tuck pointing
- Not suitable for underwater applications, permanent water immersion, or for aquariums and around swimming pools
- Not recommended for joints deeper than 1/4" without the use of a backer rod or in joints wider than 3/8"
- Do not use on mirrors or metals that will corrode

### COVERAGE

#### A 5.5 fl. oz. (163 mL) cartridge will extrude:

- A 1/4" (6 mm) bead extrudes approx. 15 ft. (4.7 m)
- A 3/8" (9.5 mm) bead extrudes approx. 6.8 ft. (2.1m)

#### A 10 fl. oz. (295 mL) cartridge will extrude:

- A 1/4" (6 mm) bead extrudes approx. 31 ft. (9.3 m)
- A 3/8" (9.5 mm) bead extrudes approx. 13.6 ft. (4.1 m)



## DIRECTIONS

### Application:

Using a caulking gun, apply steady trigger pressure forcing the sealant onto the surface and into the joint. Maximum joint size should not exceed 5/8" (15.9 mm) x 1/2" (12.7 mm). A width to depth ratio of 2:1 should be maintained. Smooth bead with a wet finger or tool. Allow to dry 30 minutes before painting with latex paint or 24 hours if using oil-based paints. Allow a minimum of 24 hours before exposing to water.

*Note: Clear sealant will extrude white and will turn clear as it dries.*

### Clean-up:

Clean tools and uncured adhesive residue immediately with warm water and soap. Cured adhesive may be carefully cut away with a sharp-edged tool.

## STORAGE & DISPOSAL

**KEEP FROM FREEZING.** Store in a cool, dry location at room temperature. For maximum shelf-life store at 75°F (24°C). Take unwanted product to an approved household hazardous waste transfer facility. Hardened material may be disposed of with trash.

## LABEL PRECAUTIONS

*For 5 oz squeeze tubes and 10 oz cartridges (Clear):*

**CAUTION!** May irritate eyes and skin. Avoid contact with eyes and skin. Do not swallow. **FIRST AID:** If swallowed, call physician or Poison Control center. For eye contact flush with water for 15 minutes. For skin contact, wash with soap and water. **KEEP OUT OF THE REACH OF CHILDREN.**



**WARNING: Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**

**Refer to the Safety Data Sheet (SDS) for further information**

*For 5 oz squeeze tubes and 10 oz cartridges (White and Almond):*

**CAUTION!** Contains ethylene glycol, butyl acetate and crystalline. May cause skin, eye, and respiratory irritation. Avoid contact with eyes and skin. Use with adequate ventilation. Do not swallow. **FIRST AID:** If swallowed, do not induce vomiting; call a physician or Poison Control center. For eye contact flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water. If overcome by vapors, get fresh air. **KEEP OUT OF THE REACH OF CHILDREN.**



**WARNING: Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**

**Refer to the Safety Data Sheet (SDS) for further information**

## DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

## LIMITED WARRANTY

This product is warranted by Henkel Corporation to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty – express or implied – including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Henkel at 1.800.624.7767 M-F 9:00 am to 4:00 pm ET.



### Trusted Performance. Proven Results.

For over 50 years, LOCTITE Brand adhesives and sealants have taken on the toughest jobs. Used in race cars, airplanes, and even in the space-shuttle, LOCTITE provides solutions for the most demanding industrial, professional and consumer applications. LOCTITE gives you the specialization, power, and performance to not only get your job done, but to get it done right.

For Technical Assistance call : 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET  
[www.loctiteproducts.com](http://www.loctiteproducts.com)



LOCTITE Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067  
[www.henkel-northamerica.com](http://www.henkel-northamerica.com)