

# PGP® ULTRA

Radius: **17' to 46'**  
Flow: **0.36 to 14.8 GPM**

The PGP Ultra raises the bar for rotor technology with powerful features developed over three decades of research, customer feedback, and lab testing.

## KEY BENEFITS

- Patented automatic arc return feature returns the turret back to the original arc pattern if vandalized; adjustable arc from 50° to 360°
- Non-strippable drive mechanism is protected from damage if turned in the opposite direction of travel
- Part- and full-circle in one model for flexibility across landscapes and reduced inventory
- Headed and slotted setscrew allows radius adjustment with a Hunter Wrench or flat-blade screwdriver
- Flat-top nozzles allow fast, easy insertion
- QuickCheck™ Arc Mechanism for fast arc adjustment

## OPERATING SPECIFICATIONS

- Nozzle choices: 34
- Radius: 17' to 46'
- Flow: 0.36 to 14.8 GPM
- Recommended pressure range: 25 to 70 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rate: 0.4 in/hr approximately
- Nozzle trajectory: standard = 25°, low-angle = 13°
- Nozzle racks: 1.5 to 8.0 blue, 2.0 to 4.5 low-angle gray, 0.50 to 3.0 black, 6.0 to 13.0 green, MPR-25, MPR-30, MPR-35
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- Drain Check Valve (up to 10' of elevation)
- Reclaimed water ID
- Blue #1.5-4.0 Nozzles

## USER-INSTALLED OPTIONS

- Drain Check Valve (up to 3' of elevation) PGP 4" / 6" only (P/N 142300SP)
- HSJ-0 prefabricated ¾" PVC Swing Joint



**PGP Ultra Reclaimed**

Available as a factory-installed option on all models



**PGP Ultra**

Easy arc and radius adjustment



### PGP-00

Overall height: 7½"  
Exposed diameter: 1¾"  
Inlet size: ¾"



### PGP-04

Overall height: 7½"  
Pop-up height: 4"  
Exposed diameter: 1¾"  
Inlet size: ¾"



### PGP-06

Overall height: 9¾"  
Pop-up height: 6"  
Exposed diameter: 1¾"  
Inlet size: ¾"



### PGP-12

Overall height: 17"  
Pop-up height: 12"  
Exposed diameter: 1¾"  
Inlet size: ¾"

## PGP-ULTRA – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
<b>PGP-00</b> = Shrub <b>PGP-04</b> = 4" pop-up <b>PGP-06</b> = 6" pop-up <b>PGP-12</b> = 12" pop-up	Adjustable arc, plastic riser, 8 standard nozzles, and 4 low-angle nozzles	<b>(blank)</b> = No option <b>CV</b> = Drain Check Valve <b>CV-R</b> = Drain Check Valve and reclaimed water ID	<b>Blue 1.5-8.0</b> <b>Gray low-angle</b> <b>Black short-radius</b> <b>Green high-flow</b> <b>MPR-25-Q, T, H, F</b> <b>MPR-30-Q, T, H, F</b> <b>MPR-35-Q, T, H, F</b> <b>1.5 to 4.0</b> = Only nozzles 1.5-4.0 can be factory-installed

### Examples:

PGP-04 = 4" pop-up, adjustable arc

PGP-04-2.5 = 4" pop-up, adjustable arc, and 2.5 nozzle

PGP-12-CV-R-4.0 = 12" pop-up, adjustable arc, with drain check valve and reclaimed water ID, and 4.0 nozzle