

SOLENOIDS

ACCESSORIES

Heavy-duty Hunter 24 VAC or latching solenoids provides dependable operation and long life performance.

Key Benefits

- Compatible with all Hunter irrigation valves
- Energy-efficient, low-power design
- Engineered with ultra-durable, heavy-duty materials for maximum longevity
- Stops water intrusion and protects critical electrical components
- Pre-wired with 18" of valve-control wire
- Captive plunger offers easy servicing of solenoid
- Manual quarter-turn on/off control
- Easy installation with no tools required


Electrical Specifications

606800

- Minimum opening/operating voltage: 19 VAC
- Maximum recommended voltage: 28 VAC
- Current at 24 VAC:
 - 350 mA inrush, 190 mA holding, 60 Hz
 - 370 mA inrush, 210 mA holding, 50 Hz
- Maximum operating pressure: 220 PSI
- Wire leads: 18' of 18 AWG UL-approved wire

458200

- Minimum opening/operating voltage: 6 VDC
- Maximum recommended voltage: 9 VDC
- Coil resistance: 4.8 ohms nominal
- Maximum operating pressure: 200 PSI
- Wire leads: 18' of 18 AWG black and red UL-approved wire



Type: AC and DC-Latching Solenoids




AC Solenoid

Height: 2¾"
Width: 1"
Depth: 1"



DC-Latching Solenoid

Height: 2¾"
Width: 1"
Depth: 1"



Model	Description
606800	AC Solenoid for all Hunter irrigation valves <small>*All PGV, ICV, and IBV valves come factory-installed with AC solenoid #606800. Use for replacement or retrofits.</small>
458200	DC-latching solenoid for all Hunter irrigation valves

User-Installed Options

Model	Description
NODE	
NODE-200	2-station controller (DC-Latching Solenoid ordered separately)
NODE-400	4-station controller (DC latching solenoid ordered separately)
NODE-600	6-station controller (DC latching solenoid ordered separately)
NODE-BT	
NODE-BT-200	2-station Bluetooth battery controller
NODE-BT-400	4-station Bluetooth battery controller
XC Hybrid	
XCH-600	6-Station indoor/outdoor controller
XCH-1200	12-Station indoor/outdoor controller
XCH-600-SS	6-Station outdoor controller, stainless steel
XCH-1200-SS	12-Station outdoor controller, stainless steel
XCH-600-SSP	6-Station outdoor controller, stainless steel, solar
XCH-1200-SSP	12-Station outdoor controller, stainless steel, solar