



DETAILS

MOUNT Wall Mount, Ceiling Mount

MATERIAL Galvanneated Steel, Stainless Steel
(Option -SS)

CONCEALED TOUCH LATCH Screwdriver Latch (SDL)

ADDITIONAL BENEFITS Contains Recycled Material,
Recyclable

SIZE OPTIONS (INCHES)

6" x 6"	16" x 16"	22" x 36"
8" x 8"	16" x 20"	24" x 24"
8" x 12"	16" x 24"	24" x 30"
10" x 10"	18" x 18"	24" x 36"
12" x 12"	18" x 24"	24" x 48"
12" x 16"	18" x 36"	30" x 30"
12" x 18"	20" x 20"	30" x 36"
12" x 24"	20" x 24"	32" x 32"
14" x 14"	20" x 30"	36" x 36"
14" x 20"	22" x 22"	36" x 48"
14" x 24"	22" x 30"	48" x 48"
15" x 15"		

DRYWALL

DRYWALL ACCESS DOORS

DW SERIES

Access door and frame shall be fabricated from 16 gage, galvanneated steel with a prime coat finish suitable for painting. The door shall have rounded safety corners and a rod hinge up to 24", 24" and larger are provided with a concealed piano hinge. Frame shall be one piece construction with no mitres or welds on the face. Latch shall be screwdriver operated.

Standard material thickness is 16 gage for the door and door frame. A heavy duty version is also available with 14 gage thickness for the door and door frame.

FUNCTION

Doors are ideally suited for new installations or for remodeling, in masonry, tile, wood or other wall and ceiling surfaces. Door features rounded safety corners.

OPTIONAL FINISH

SS- Stainless Steel

OPTIONAL LATCHES



AKL- Allen
Key Latch



CL- Cylinder
Key Lock



CLD- Cylinder
Lock with
Dust Shutter



MLP- Mortise
Cylinder Lock



TH- T-Handle