

**Product**

**AutoSnap® Straight Fitting (Female-NPT) Assembly for TracPipe® and TracPipe® CounterStrike®**

**Project Information**

Job Name:	Date Submitted:
Location:	Submitted By:
Engineer:	Approved By:
Contractor:	Manufacturer's Rep:

**Installation**

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

**Application Information**

Transition fitting between TracPipe or CounterStrike Tubing and NPT thread. Fitting thread is Female NPT. For use indoors, outdoors, and concealed location applications.

**Technical Data**

Materials

Nut, Adapter, Flange and Snap Ring      Yellow Brass

Pressure Ratings (used with tubing)

Specification Operating Pressure      25 PSIG  
 CSA International Evaluation Report - Max Operating Pressure  
 3/8" through 1-1/4"      125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range      -20 to 200 Deg F



**Codes**

ICC Codes (IFGC, IRC, IMC), NFPA 54 / ANSI Z223.1, UPC, CAN/CSA B149.1, NFPA 58, UPC

**Standards**

ANSI LC1 / CSA 6.26, ANSI Z223.1

**Listings**

CSA, ICC PMG 1046 / 1052, IAPMO (UPC) File No. 4665

**Dimensional Information**

✓	Size	P/N	Diameter across flats (Nom. in.)	Fitting length (Nom. in.)	TracPipe or CounterStrike Size	Weight (lbs/ft)
<input type="checkbox"/>	3/8" x 1/2"	FGP-SFSTF-375	7/8"		3/8"	0.25
<input type="checkbox"/>	1/2"	FGP-SFSTF-500	1"		1/2"	0.29
<input type="checkbox"/>	3/4"	FGP-SFSTF-750	1-1/4"		3/4"	0.43
<input type="checkbox"/>	1"	FGP-FSTF-1000	1-3/4"		1"	0.78

OmegaFlex, Inc. \* 451 Creamery Way\* Exton, PA 19341

Tel: 610-524-7272 \* Toll Free: 800-671-8622 \* Fax: 610-524-7282

www.omegaflex.com