





| Product | | | | |
|--|---|----------------------------|--|--------------|
| Striker Plates | 1 | | | |
| Project Informat | tion | | | |
| Job Name: | | | Date Submitted: | |
| Location: | | | Submitted By: | |
| Engineer: Contractor: | | | Approved By: Manufacturer's Rep: | |
| Installation | | | vianuracturer s nep. | |
| | d in accordance with the TracPi | ine Design Guide and Inst | allation Instructions and all applicable codes | |
| Application Info | | pe Design Galac and mist | anation instructions and an applicable codes | |
| | Potential Puncture | | | |
| Technical Data | | | | |
| <u> Materials</u> | | | | |
| Hardened Steel I | RB >75 | | | |
| Pressure Ratings | s (used with tubing) | | | |
| N/A | <u>- (4364 min (42))</u> | | | |
| Temperature Ratings (used with tubing) Operating Temperature Range | | N/A | | |
| Codes | | | | |
| | , IRC, IMC, IPC), NFPA 54 , UPC, | CAN/CSA B149.1, NFPA 5 | 58, UPC | |
| Standards | | | | |
| | 5.26, ANSI Z223.1 | | | |
| Listings | ,, ,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | | | |
| _ | 046 / 1052/ 1058 IAPMO (UPC) | V 5:10 No 2602 / 4665 / ES | ED 0227 | |
| | | FIIE NO.3062 4003 L3 | 5 ER-U227 | |
| Dimensional Info | ormation | | | |
| \checkmark | | | | |
| | P/N | LxW | | Weight (lbs) |
| | FGP-SP-025 | 1-1/2" x 3" | | 0.1 |
| | FGP-SP-050 | 6-1/2" x 3" | | 0.3 |
| | FGP-SP-075 | 8" x 3" | | 0.4 |
| | FGP-SP-100 | 11-1/2" x 3" | | 0.6 |
| | | | | |
| | FGP-SP-617 | 17" x 6-1/2" | | 1.8 |
| | | | | |
| | | | | |