

RESIDENTIAL & COMMERCIAL IRRIGATION Built on Innovation®



- **Flexible design:** Modular station expansion allows for conventional wiring from 4 to 23 stations
- **Two-wire compatible:** Enable hybrid two-wire control for up to 32 stations with EZ-1 Decoders
- **Enhanced sensor functionality:** Two sensor inputs are available for use with Hunter Solar Sync® and Clik Sensors

PRO-C® CONTROLLER

The Professional's Choice For Residential And Light Commercial Systems

The next generation of Pro-C Controllers is here! With the new **P2C Series**, you get all the features of the popular Pro-C line — like flexible station counts and simple programming — plus an updated user interface, large backlit display, and improved sensor and operational functionality.

As the professional's choice for decades, the reliable Pro-C Controller provides powerful, yet affordable irrigation management with convenient expansion options in a compact package. Users can choose from conventional wiring, innovative EZ Decoder control, or hybrid conventional/two-wire operations. Ideal for residential and light commercial landscape projects, the Pro-C provides the ultimate flexibility for new projects, retrofits, or landscape expansions.

Pro-C Controllers are EPA WaterSense® approved when paired with a Hunter Solar Sync Sensor, which enables daily adjustments based on local weather conditions for maximum water savings.



PRO-C FEATURES & SPECIFICATIONS

Key Benefits

- · Number of stations:
- Modular Pro-C Controller
 - Conventional wiring from 4 to 23 stations
 - Hybrid EZ Decoder option for up to 32 total stations (28 stations maximum if two-wire only)
- 3 automatic irrigation programs with 4 start times per program and 6-hour run times per station
- 2 sensor inputs available for use with Solar Sync or any Clik Sensors
- 1 P/MV output for pump start relay and master valve activation
- High-visibility, backlit display for simple programming in any light
- Optional Seconds Mode allows for station run times with seconds resolution from 1 second to 5 minutes
- Easy Retrieve® Memory allows for manual backup and retrieval of preferred settings and programming
- QuickCheck™ Technology provides simple diagnostics of faulty field wiring
- Backward compatible with previous modular PC-400 models dated 2014 to 2023

Operating Specifications

- · Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: IP44 (outdoor), UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 2 years

PRO-C	
Model	Description
P2C-400	4-station base, plastic wall mount cabinet with cable and plug
PCM-300	3-station plug-in module
PCM-900	9-station plug-in module
PCM-1600	16-station plug-in module
PC-DM	EZ Decoder output module

Model

Plastic Outdoor

Height: 9" Width: 10" Depth: 4½"







PCM300

PCM900





PCM1600

PC-DM



EPA WaterSense

Add the WaterSense® labeled Solar Sync Sensor to improve the water efficiency of this controller.

 $\textbf{Website} \ \ \text{hunterindustries.com} \ \ | \ \ \textbf{Customer Support} \ \ 1-800-383-4747 \ \ | \ \ \textbf{Technical Service} \ \ 1-800-733-2823$

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.