B3104 - Light-Duty Clevis Hanger B3104F - Light-Duty Clevis Hanger - Felt Lined B3104C - Light-Duty Clevis Hanger - PVC Coated

Size Range: 1/2" (15mm) to 4" (100mm) pipe Material: Steel


Function: Recommended for the suspension of light stationary pipe allowing for vertical adjustment.

Approvals: Underwriter's Laboratories Listed in the USA **(UL)** and Canada **(cUL)** for sizes ³/4" (20mm) thru 4" (100mm). Conforms to Federal Specification WW-H-171E & A-A-1192A, Type 12 and Manufacturers Standardization Society ANSI/MSS SP-69 & SP-58, Type 1.

Standard Finish: Plain, Electro-Galvanized, or DURA-GREEN[™]


Order By: Part number and finish.





*Slide-Rite[™] Clevis Hanger design for sizes 2, 3 & 4.

Pat. No. 5,848,770 5,924,655



Center of pipe to bottom of hanger rod. E

Minimum thread length of hanger rod.

F Adjustment Top of cross bolt to bottom of hanger rod nut inside the hanger.



B3104C



B3104F

		Nominal Pipe Size		e Rod Size	Rod Size B		C
_	Part No.	in.	(mm)	Α	in.	(mm)	in. (mm)
	B3104- ¹ /2	1/2"	(15)	³ /8"-16	1 ¹⁵ /16"	(49.2)	1 ¹ /2" (38.1)
	B3104- ³ /4	3/4"	(20)	³ /8"-16	2 ⁵ /16"	(58.7)	1 ³ /4" (44.4)
	B3104-1	1"	(25)	³ /8"-16	2 ³ /4"	(69.8)	2 ¹ /16" (52.4)
	B3104-1 ¹ /4	1 ¹ /4"	(32)	³ /8"-16	3 ⁵ /16"	(84.1)	2 ⁷ /16" (61.9)
	B3104-1 ¹ /2	1 ¹ /2"	(40)	³ /8"-16	35/8"	(92.1)	2 ⁵ /8" (66.7)
	B3104-2 *	2"	(50)	³ /8"-16	4 ¹³ /16"	(122.2)	3 ⁵ /8" (92.1)
	B3104-2 ¹ /2	21/2"	(65)	¹ /2"-13	5 ¹³ /16"	(147.6)	4 ⁵ /16" (109.5)
	B3104-3 *	3"	(80)	¹ /2"-13	6 ⁷ /16"	(163.5)	4 ⁵ /8" (117.5)
	B3104-3 ¹ /2	3 ¹ /2"	(90)	¹ /2"-13	6 ¹⁵ /16"	(176.2)	4 ¹⁵ /16" (125.4)
_	B3104-4 *	4"	(100)	¹ /2"-13	7 ³ /4"	(196.8)	5 ¹ /2" (139.7)

Part No.	Rod Tak in.	(mm)	in.	E (mm)	Adjust in.	ment F (mm)	Desig Lbs.	n Load (kN)	Approx Lbs.	Wt./100 (kg)
B3104-¹/ 2	13/16"	(20.6)	2 ¹ /2"	(63.5)	7/16"	(11.1)	150	(.67)	13	(5.9)
B3104- ³ /4	1"	(25.4)	2 ¹ /2"	(63.5)	7/16"	(11.1)	250	(1.11)	22	(10.0)
B3104-1	1 ³ /8"	(34.9)	2 ¹ /2"	(63.5)	⁹ /16"	(14.3)	250	(1.11)	24	(10.9)
B3104-1 ¹ /4	1 ³ /4"	(44.4)	2 ¹ /2"	(63.5)	¹³ /16"	(20.6)	250	(1.11)	29	(13.1)
B3104-1 ¹ /2	2"	(50.8)	2 ¹ /2"	(63.5)	1"	(25.4)	250	(1.11)	30	(13.6)
B3104-2 *	2 ¹⁵ /16"	(74.6)	2 ¹ /2"	(63.5)	1 ³ /4"	(44.4)	250	(1.11)	35	(15.9)
B3104-2 ¹ /2	37/16"	(87.3)	2 ¹ /2"	(63.5)	2"	(50.8)	350	(1.55)	82	(37.2)
B3104-3 *	33/4"	(95.2)	2 ¹ /2"	(63.5)	2"	(50.8)	350	(1.55)	91	(41.3)
B3104-3 ¹ /2	4"	(101.6)	2 ¹ /2"	(63.5)	2"	(50.8)	350	(1.55)	98	(44.4)
B3104-4 *	4 ⁹ /16"	(115.9)	21/2"	(63.5)	2 ³ /16"	(55.6)	400	(1.78)	132	(59.9)

All dimensions in charts and on drawings are in inches. Dimensions shown in parentheses are in millimeters unless otherwise specified.